



Tech & Data Sheet

ANTIQUING AGENT

TOLL FREE (866) 854-8881

www.decorativecs.com

METHOD 1

This method of antiquing requires using clear liquid release during the stamping process then coming back the next day when the stamped surface is dry to apply the antiquing.

1. Proceed by mixing approximately 1 tablespoon of Antiquing Agent per each gallon of cool clean water and mixing completely. More Antiquing Agent can be used to achieve the desired color, but use no more than 4 tablespoons per gallon as this method is mainly for lighter applications, as imparting too many loose pigment solids onto the surface will inhibit the Clear Seal penetration into the substrate. This method will impart a color infusion mainly in the grout lines and low areas. It is easier to remove if over applied and generates no odors or fumes. Once material is mixed, use a low pressure sprayer with a fine/medium spray nozzle to lightly spray the surface. Allow to completely dry. Once dry, a second touch-up coat can be applied if needed.
2. Apply Clear Seal by sprayer or roller to the surface, being careful not to over-work the surface and lift out any Antiquing Agent. Subsequent coats can be applied once each coat has fully dried.

METHOD 2

For outdoor jobs, one method of antiquing is to spray colored liquid release agent over the surface just prior to stamping instead of using clear liquid release.

1. After stamping a section (approximately 50 square feet), spray more colored liquid release over the freshly stamped area to achieve the look desired or allow it to puddle in the low areas of the texture. If necessary, add more antique powder (up to 4oz per gallon of liquid release) to make the antiquing color darker or add more clear liquid release agent to make the color lighter. Once you achieve the antique look desired, move on to the next area. It is important to mix each batch of colored liquid release the same and to spray each section the same in order to achieve a uniform antique look over the entire surface. How the antiquing looks over the stamped concrete while wet is how it will look when sealed. As the stamped concrete dries and the liquid release evaporates, the colors of the stamped concrete and the antiquing color will fade lighter.
2. When sealed with a solvent based Clear Seal, the colors will come back to how they looked when wet. **Always practice on a sample board to perfect the look you want and have it approved by the customer before doing a job.** Allow the material and liquid release agent to dry completely (no damp spots) before sealing with a concrete sealer. Thin-Stamp can be sealed 24 hours after stamping, Integral Color and Color Hardener requires approximately 14 days to cure.

IMPORTANT NOTICE:

These products are sold subject only to the expressed warranties contained herein. Additional warranties, expressed or implied, and any warranty of merchantability is hereby excluded. Buyer agrees that seller assumes no liability for consequential damages of any kind, which result from the use or misuse of the merchandise sold hereunder. In the event that the buyer proves that any goods received do not conform to the specifications agreed to between the parties or if the buyer proves that such good were defectively manufactured, the buyer's remedies shall be limited to either the return of the good and repayment of the purchase price or replacement of the nonconforming good at the option of the seller. Such remedy being exclusive of all others and the sole remedy available to the buyer, hereby expressly waives any claim to additional damages.