



Tech & Data Sheet

HIGH GLOSS WAX

Phone: 972.242.8881

www.decorativecs.com

PRODUCT DESCRIPTION

High Gloss Wax is a high-gloss, non-yellowing acrylic floor polish for use on all types of INTERIOR sealed floors. It not only dries to a high gloss wet look finish, it can be maintained at ultra high gloss with a hardwood floor mop or by high speed burnishing.

BENEFITS

- **High Gloss Wax** produces beautiful high-gloss, wet look shine upon drying, without buffing
- Buffs up to a super shine using high speed or ultra high speed burnishing. Easy to maintain with minimal labor. **High Gloss Wax** does not powder or dust on burnishing
- Highly detergent resistant. **High Gloss Wax** is not harmed by repeated scrubbing with a neutral detergent, or damp mopping between buffings
- Restore worn areas by re-coating. Just apply and let dry
- **High Gloss Wax** is highly slip resistant and meets the **ASTM D-2407** requirement for slip resistance
- **High Gloss Wax** is economical. One gallon covers over 1500 square feet per coat and lasts for months without re-coating

ENVIRONMENTAL IMPACT

High Gloss Wax contains no toxic heavy metals or butyl solvents and has very low VOC's

HOW TO USE

- 1) Clean floor with warm water and let dry completely.
- 2) Spread **High Gloss Wax** in a thin and even coat over the floor using a hardwood floor mop. Allow to dry completely (about 25-30 minutes). You may apply a second coat if desired.
- 3) You may apply over old coats of wax. *NOTE: Floor must be sealed for at least 10 days before applying wax.*

PROPERTIES

Type: Super acrylic floor polish

Color: Colorless, non-yellowing

Odor: Very Mild

Toxicity: Non-toxic – Do not take internally

Flammability: Non-flammable

pH: 8.5 – 8.9

Composition: Acrylic polymer emulsion, ethylene co-polymers, proprietary additives and quality control agents